PUMA40

Power wheelchair for indoor/outdoor use



Puma 40. An award-winning benchmark for the way ahead. With Puma 40, Handicare introduces a new generation power wheelchairs for intensive use indoors and outdoors. Truly modular in design, Puma 40 offers you the flexibility you need to create a perfect fit for each client and their lifestyle. With ease and cost-effectively. Available in front and rear wheel drive, Puma 40 delivers comfortable and stable driving at all speeds due to the adjustable Full Track Suspension System (FTSS) and a choice of renowned electronics. High speed and a large range with 74 Ah battery option. Powerful motors and high torque ensure great manoeuvrability. Compact design and low seat height for maximum independence indoors. The award-winning Sedeo seating system offers a new level of seating comfort, combining high adjustability with a wide range of interchangeable options. Full range of electrical options available. All of this and it also looks great! Handicare's Puma 40, a perfect blend of functionality, comfort and design.



PUMA40





Full Track Suspension System





Excellent driving indoors and outdoors

The Puma 40, available as front and rear wheel drive, is designed for intensive use. Its state-of-theart Full Track Suspension System (FTSS) coupled with the adjustable centre of gravity delivers a smooth and stable ride with maximum traction at all speeds. Powerful motors and high torque ensure great manoeuvrability. Compact design and low seat height for maximum independence indoors.

Ergonomic comfort

The award-winning Sedeo Pro seating system offers a new level of seating comfort due to high adjustability and a wide choice of interchangeable support and positioning options. Adjustable FTSS suspension, combining rubber shock absorbers with a unique swivel suspension bridge, enhances a comfortable driving experience.

Stylish design with a personal touch

Characteristic for the Puma 40 are its looks. A perfect blend of functionality and design, this power wheelchair comes in a choice of two stylish base frame colours and four complimentary accent colours. Allows for easy personalisation to fit the individual's lifestyle.

Total flexibility, easy to work with

Truly modular in design, Puma 40 offers you the flexibility you need to create a perfect fit for every client, also in case of changing needs or re-use. If you know one product, you know them all. Easy to work with, easy to service. Less stock required.

Total weight excl. batteries kg stone 97.6 15.4 97.6 15.4 Total weight incl. batteries kg stone 126 (40 Ah) 19.9 (40 Ah) 126 (40 Ah) 19.9 (Total length incl. legrests mm inch 1190 46.9 1115 43.9 Total width 13" drive wheels mm inch 610 24 610 24 Total width 14" drive wheels mm inch 655 25.8 655 25.8 Seat angle ° ° 0 - 6 0 - 6 0 - 6 0 - 6 Seat depth (effective) mm inch 420 - 600 16.5 - 23.6 420 - 600 16.5 - 23.6 Seat width (effective) mm inch 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 Seat height excl. cushion (2) mm inch 485 19.1 485 19.1 Backrest angle ° ° 89 - 128 89 - 128 89 - 128 89 - 12 Backrest height mm inch 500 - 640 19.7 - 25.2 500 - 640 19.7 - 25.2 Diameter castor wheels mm inch 330 / 350 13 / 14 330 / 350 13 / 14 PERFORMANCE Maximum speed km/h mph 6 / 10 3.7 / 6.2 6 / 10 3.7 / 6.2 Range (ISO 7176-4), 6 km/h km miles 36 (74 Ah) 22.4 (74 Ah) 36 (74 Ah) 22.4	
Total weight excl. batteries kg stone 97.6 15.4 97.6 15.4 Total weight incl. batteries kg stone 126 (40 Ah) 19.9 (40 Ah) 126 (40 Ah) 19.9 (Total length incl. legrests mm inch 1190 46.9 1115 43.9 Total width 13" drive wheels mm inch 610 24 610 24 Total width 14" drive wheels mm inch 655 25.8 655 25.8 Seat angle ° ° 0 - 6 0 - 6 0 - 6 0 - 6 Seat depth (effective) mm inch 420 - 600 16.5 - 23.6 420 - 600 16.5 - 23.6 Seat width (effective) mm inch 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 Seat height excl. cushion (2) mm inch 485 19.1 485 19.1 Backrest angle ° ° 89 - 128 89 - 128 89 - 128 89 - 128 89 - 128 Backrest height mm inch 500 - 640 19.7 - 25.2 500 - 640 19.7 - 25.2 Diameter castor wheels mm inch 330 / 350 13 / 14 330 / 350 13 / 14 PERFORMANCE Maximum speed km/h mph 6 / 10 3.7 / 6.2 6 / 10 3.7 / 6.8 Range (ISO 7176-4), 10 km/h km miles 27 (74 Ah) 16.8 (74 Ah) 27 (74 Ah) 16.8 (Obstacle height (outdoor) mm inch 60 2.4 80 3.1 Ground clearance mm inch 70 2.8	
Total weight incl. batteries kg stone 126 (40 Ah) 19.9 (40 Ah) 126 (40 Ah) 19.9 (40 Ah) 126 (40 Ah) 19.9 (40	/60/74
Total length incl. legrests mm inch 1190 46.9 1115 43.9 Total width 13" drive wheels mm inch 610 24 6610 24 Total width 14" drive wheels mm inch 655 25.8 Seat angle ° ° 0 - 6 0 - 6 0 - 6 0 - 6 Seat depth (effective) mm inch 420 - 600 16.5 - 23.6 420 - 600 16.5 - 23.6 Seat width (effective) mm inch 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 Seat height excl. cushion (2) mm inch 415 16.3 415 16.3 Seat height incl. cushion (2) mm inch 485 19.1 485 19.1 Backrest angle ° 89 - 128 89 - 128 89 - 128 89 - 128 89 - 1 Backrest height mm inch 500 - 640 19.7 - 25.2 500 - 640 19.7 - 25.2 Diameter castor wheels mm inch 330 / 350 13 / 14 330 / 350 13 / 14 PERFORMANCE Maximum speed km/h mph 6 / 10 3.7 / 6.2 6 / 10 3.7 / 6.8 Range (ISO 7176-4), 16 km/h km miles 36 (74 Ah) 22.4 (74 Ah) 36 (74 Ah) 22.4 (74 Ah) 16.8 (Obstacle height (outdoor) mm inch 60 2.4 80 3.1 Ground clearance mm inch 70 2.8 70 2.8	
Total width 13" drive wheels mm inch 610 24 610 24 Total width 14" drive wheels mm inch 655 25.8 Seat angle ° ° 0 - 6 0 - 6 0 - 6 0 - 6 Seat depth (effective) mm inch 420 - 600 16.5 - 23.6 420 - 600 16.5 - 6 Seat width (effective) mm inch 400 - 540 15.7 - 21.3	40 Ah)
Total width 14" drive wheels mm inch 655 25.8 655 25.8 Seat angle ° ° 0 - 6 0 - 6 0 - 6 0 - 6 0 - 6 Seat depth (effective) mm inch 420 - 600 16.5 - 23.6 420 - 600 16.5 - 6 Seat width (effective) mm inch 400 - 540 15.7 - 21.3 400 - 540 15.7	
Seat angle ° ° 0 - 6 16.5 Seat width (effective) mm inch 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 16.3 415 16.3 415 16.3 415 16.3 415 16.3 415 16.3 415 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1	
Seat depth (effective) mm inch 420 - 600 16.5 - 23.6 420 - 600 16.5 - 23.6 420 - 600 16.5 - 23.6 420 - 600 16.5 - 23.6 420 - 600 16.5 - 23.6 420 - 600 16.5 - 23.6 420 - 600 16.5 - 23.6 420 - 600 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 400 - 540 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 485 19.1 <td></td>	
Seat width (effective) mm inch 400 - 540 15.7 - 21.3 400 - 540 15.7 - 21.3 Seat height excl. cushion (2) mm inch 415 16.3 415 16.3 Seat height incl. cushion (2) mm inch 485 19.1 485 19.1 Backrest angle ° ° 89 - 128	
Seat height excl. cushion (2) mm inch 415 16.3 415 16.3 Seat height incl. cushion (2) mm inch 485 19.1 485 19.1 Backrest angle ° 89 - 128 <t< td=""><td>23.6</td></t<>	23.6
Seat height incl. cushion (2) mm inch 485 19.1 485 19.1 Backrest angle ° ° 89 - 128 80 - 131 81 / 128 80 - 128	21.3
Backrest angle ° 89 - 128 9 - 10 230 / 255 9 / 10 230 / 255 9 / 10 230 / 255 9 / 10 230 / 255 9 / 10 230 / 255 9 / 10 230 / 255 9 / 10 230 / 255 9 / 10 230 / 255 9 / 10 230 / 255 9 / 10 230 / 255 9 / 10 230 / 255 9 / 10 230 / 255 9 / 10 230 / 350 13 / 14 330 / 350 13 / 14 330 / 350 13 / 14 330 / 350 13 / 14 330 / 350 13 / 14 </td <td></td>	
Backrest height mm inch 500 - 640 19.7 - 25.2 500 - 25.2 500 - 25.	
Diameter castor wheels mm inch 230 / 255 9 / 10 230 / 255 9 / 10 Diameter drive wheels mm inch 330 / 350 13 / 14 330 / 350 13 / 14 PERFORMANCE Maximum speed km/h mph 6 / 10 3.7 / 6.2 6 / 10 3.7 / 6.2 Range (ISO 7176-4), 6 km/h km miles 36 (74 Ah) 22.4 (74 Ah) 36 (74 Ah) 22.4 (74 Ah) 16.8 (74 Ah) 22 (74 Ah) 16.8 (74 Ah) 27 (74 Ah) 16.8 (74 Ah) 28 (74 Ah) <t< td=""><td>28</td></t<>	28
Diameter drive wheels mm inch 330 / 350 13 / 14 330 / 350 13 / 14 PERFORMANCE Maximum speed km/h mph 6 / 10 3.7 / 6.2 6 / 10 3.7 / 6.2 Range (ISO 7176-4), 6 km/h km miles 36 (74 Ah) 22.4 (74 Ah) 36 (74 Ah) 22.4 (74 Ah) Range (ISO 7176-4), 10 km/h km miles 27 (74 Ah) 16.8 (74 Ah) 27 (74 Ah) 16.8 (74 Ah) Obstacle height (outdoor) mm inch 60 2.4 80 3.1 Ground clearance mm inch 70 2.8 70 2.8	25.2
PERFORMANCE Maximum speed km/h mph 6 / 10 3.7 / 6.2 6 / 10 3.7 / 6.2 Range (ISO 7176-4), 6 km/h km miles 36 (74 Ah) 22.4 (74 Ah) 36 (74 Ah) 22.4 (74 Ah) Range (ISO 7176-4), 10 km/h km miles 27 (74 Ah) 16.8 (74 Ah) 27 (74 Ah) 16.8 (04 Ah) 27 (74 Ah)	
Maximum speed km/h mph 6 / 10 3.7 / 6.2 6 / 10 3.7 / 6.2 Range (ISO 7176-4), 6 km/h km miles 36 (74 Ah) 22.4 (74 Ah) 36 (74 Ah) 22.4 (74 Ah) 36 (74 Ah) 22.4 (74 Ah) 16.8 (74 Ah) 27 (74 Ah) 16.8 (74 Ah) 28 3.1 Ground clearance mm inch 70 2.8 70 2.8	4
Range (ISO 7176-4), 6 km/h km miles 36 (74 Ah) 22.4 (74 Ah) 36 (74 Ah) 22.4 (74 Ah) Range (ISO 7176-4), 10 km/h km miles 27 (74 Ah) 16.8 (74 Ah) 27 (74 Ah) 16.8 (04 Ah) 16.8 (0	
Range (ISO 7176-4), 10 km/h km miles 27 (74 Ah) 16.8 (74 Ah) 27 (74 Ah) 16.8 (00 Ah) Obstacle height (outdoor) mm inch 60 2.4 80 3.1 Ground clearance mm inch 70 2.8 70 2.8	3.2
Obstacle height (outdoor) mm inch 60 2.4 80 3.1 Ground clearance mm inch 70 2.8 70 2.8	74 Ah)
Ground clearance mm inch 70 2.8 70 2.8	74 Ah)
Reversing distance mm inch 1200 47.2 1330 52.4	
The vertical ing distance that the second in	
ELECTRICAL OPTIONS	
Electrical backrest adjustment ° ° 89 - 128 89 - 128 89 - 128 89 - 1	28
Electrical tilt adjustment ° ° 0 - 45 0 - 45 0 - 45 0 - 45	
Electrical high low mm inch 0 - 300 0 - 11.8 0 - 300 0 - 11	.8
Electrical legrests ° ° 70 70 70 70	

ISO 7176-19

 ϵ

EN12182

EN12184

- 1. Affects seat height (min. seat height + 25 mm) 2. Seat height incl. load, 0° seat angle and 14" drive wheels

PUMA 20/40: The smart modular power wheelchair concept

With Puma 20/40 Handicare introduces the ultimate modular power wheelchair concept. It offers you the flexibility you need to create a perfect fit - with you local market needs, and with the specific needs and lifestyle of your clients. With ease and cost-effectively. Naturally, Handicare quality and safety are guaranteed.



